



X-IT Asphalt Release Agent provides excellent lubricating properties preventing asphalt, sealant, tar and oil build-up on truck beds, shovels, rakes, pavers, rollers, brooms, mauls, lutes and chip sealing equipment. Specifically designed for versatility, X-IT Asphalt Release Agent is engineered to offer the best slipping for easy release of all types of asphalt mixes without affecting the mix. Superior to currently available products, this advanced formula is also effective in protecting equipment against the wear and tear of hot mix asphalt.

The chosen alternative for eliminating the use of diesel fuel and more effective than detergent, pine, citrus or soy based products. X-IT Asphalt Release Agent is a non-petroleum based, non-hazardous, non-toxic, non-VOC, low odor technology satisfying worker safety and regulatory compliance goals without sacrificing performance.

USAGE INSTRUCTIONS

X-IT Asphalt Release Agent can be dispensed using valve proportioners or any other type of suitable dispensing equipment. Spray at full strength directly on truck beds and other equipment with spray application.

PHYSICAL & CHEMICAL PROPERTIES

Solubility in Water	Soluble
Odor	Very Mild
Appearance	White Liquid
pH	6.8 - 7.8
Flash Point	None
Biodegradability	Biodegradable
Corrosive	No
Specific Gravity	1.01
Vapor Density (AIR=1)	1

STORAGE

Freezing point is 0°C (32°F), if stored at a temperature below 0°C, product should be warmed above the freezing point before use. Product is non flammable and is not considered a fire hazard, better if stored away from direct sun light at temperatures below 120° F.

ENVIRONMENTAL, HEALTH AND SAFETY

X-IT Asphalt Release Agent is non-toxic, non-hazardous and biodegradable. As with the use of any chemical product, the manufacturer recommends that users review the Material Safety Data Sheet prior to use.

Skin: Generally, the product is not harmful to skin, in very rare cases it may cause minor skin irritation. Wash thoroughly with hand soap and rinse with water. If irritation persists seek medical attention.

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. Get medical attention immediately.

Ingestion: Do not induce vomiting. Seek medical assistance.

Inhalation: Remove patient to fresh air. If continued difficulty of breathing is experienced, seek medical attention immediately. If breathing stops give artificial respiration.

Spill response: Cover with suitable absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE TREATMENT

There are no federal regulations restricting the disposal of X-IT Asphalt Release Agent into municipal wastewater systems. However, please consult with your local municipality before disposing of product.

Each application is unique in its potential for contaminants and should be considered on an individual basis. If there is sufficient potential for contamination that may be regulated by a government agency, test a sample for the suspected contaminants prior to disposal.

TESTED SAFE ON	PRODUCT FEATURES
Stainless Steel and Steel	Non-Toxic, Biodegradable
Cadmium	Low Flammability
Titanium	Non-Hazardous
Aluminum	Non-Corrosive
Brass/Copper	Non-Ozone Depleting
Acrylics	No Offensive Odor
All Plastics and Rubber	Free of Phenols, Phosphates, Heavy Metals
Concrete	
	No Skin Irritation
	Non-Carcinogenic
	Freeze Thaw Stable